

Particleboard Core Doors

Neutral Pressure, Positive Pressure
Standard Models: DSP

Marshfield Accent Series®

Product Features
and Specifications

Interior Use Only

Thickness

1-3/4"; 1-3/8"

Maximum Size

	ITS-WH and UL – Max 20 Minute				
	Non Rated	NP	Cat. A (PP)	Cat. A (PPAF)	Cat B (PPFM)
Single	4/0 x 8/0	4/0 x 8/0	4/0 x 8/0	4/0 x 8/0	4/0 x 8/0
Pair	8/0 x 8/0	8/0 x 8/0	8/0 x 8/0	8/0 x 8/0	8/0 x 8/0
DE Pair	8/0 x 8/0	8/0 x 8/0	8/0 x 8/0	N/A	8/0 x 8/0
1-3/8" Single	4/0 x 8/0	3/0 x 7/0	N/A	N/A	3/0 x 7/0

Minimum Size

1/5-3/4 x 6/0

Faces

- Wood Veneer
- Primed Hardboard

Stiles

Manufacturer's standard construction per label service listing

Top and Bottom Rails

Manufacturer's standard construction per label service listing

**Face & Core
Assembly Adhesive**

Per requirements of WDMA I.S. 1A, C-6

Core

Particleboard (which complies with ANSI A208.1)

Lite Openings

See Appendix I

Factory Finish

- Enviroclad UV® finish
- Prime
- Opaque

Warranty

5-year. No exterior warranty
Option: Full; life of original installation. No exterior warranty

**Environmental Options &
LEED Credit Contribution**

- MR 4-Recycled Content — all models
- MR 5-Regional Materials — all models
(Project must be within 500 miles of Marshfield, WI)

The mark of excellence™ 

Note: Marshfield DoorSystems doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.