

Material Safety Data Sheet



Wood Dust

Marshfield DoorSystems, Inc
1401 E Fourth St
Marshfield WI 54449

Emergency Phone: (715) 486-2286
Additional Information: (715) 486-2286
CHEMTREC: (800) 924-9300

1. Product Identification

Product	Manufacturing Location
Wood Dust (untreated)	Various

Synonyms: Wood Flour, Sawdust, Sander Dust.

2. Hazardous Ingredients/Identity Information

Name	CAS#	Percent	Agency	Exposure Limits	Comments
Wood	None	100	OSHA	PEL-TWA 15 mg/m ³	Total dust
			OSHA	PEL-TWA 5 mg/m ³	Respirable dust fraction
			ACGIH	TLV-TWA 5 mg/m ³	Softwood total dust
			ACGIH	TLV-STEL 10 mg/m ³	Softwood total dust
			ACGIH	TLV-TWA 1 mg/m ³	Selected hardwood total dust (beech, oak, others)
			Recommended ¹	PEL-TWA 5 mg/m ³	Softwood or hardwood total dust
			Recommended ¹	PEL-STEL 10 mg/m ³	Softwood or hardwood total dust
Recommended ¹	PEL-TWA 2.5 mg/m ³	Western red cedar total dust			

¹ Marshfield DoorSystems recommended exposure limits based on 1989 OSHA PELs. In 1992, the U.S. Court of Appeals for the Eleventh Circuit Court overturned OSHA's 1989 Air Contaminants Rule, which included specific PELs for wood dust established by OSHA at that time. Wood dust is now officially regulated as an organic dust in a category known as "Particulates Not Otherwise Regulated" (PNOR), or Nuisance Dust. However, a number of states have incorporated the OSHA PELs from the 1989 standard in their state plans. Additionally, OSHA has announced that it may cite companies under the OSH Act general duty clause under appropriate circumstances for noncompliance with the 1989 PELs.

3. Hazard Identification

Appearance and Odor: Light- to dark-colored granular solid. Wood dust may have a slight aromatic odor. Color and odor depend on the wood species and time since dust was generated. The wood component may consist of alder, aspen, beech, birch, cottonwood, fir, gum, hemlock, hickory, maple, oak, pecan, pine, poplar, spruce, walnut, and/or Western red cedar.

Primary Health Hazards: The primary health hazard posed by this product is thought to be due to inhaling wood dust.

Primary Route(s) of Exposure:

- () Ingestion:
- (x) Skin: Dust
- (x) Inhalation: Dust

Medical Conditions Generally Aggravated by Exposure: Wood dust may aggravate preexisting respiratory conditions or allergies.

3. Hazard Identification, cont.

Chronic Health Hazards: Wood dust, depending on the species, may cause allergic contact dermatitis and respiratory sensitization with prolonged, repetitive contact or exposure to elevated dust levels. Prolonged exposure to wood dust has been reported by some observers to be associated with nasal cancer.

Carcinogenicity Listing:

- | | |
|--|--------------------|
| <input type="checkbox"/> NTP: | Not listed |
| <input checked="" type="checkbox"/> IARC Monographs: | Wood dust, Group 1 |
| <input type="checkbox"/> OSHA Regulated: | Not listed |

IARC - Group 1: Carcinogenic to Humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma of the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum.

4. Emergency and First-Aid Procedures

Ingestion: Not applicable under normal use.

Eye Contact: Wood dust may cause mechanical irritation. Treat dust in eye as foreign object. Flush with water to remove dust particles. Get medical help if irritation persists.

Skin Contact: Wood dust of certain species can elicit allergic contact dermatitis in sensitized individuals, as well as mechanical irritation resulting in erythema and hives. Get medical help if rash, irritation, or dermatitis persists.

Skin Absorption: Not known to occur under normal use.

Inhalation: Wood dust may cause obstruction in the nasal passages, resulting in dryness of nose, dry cough, sneezing, and headaches. Remove to fresh air. Get medical help if persistent irritation, severe coughing, or breathing difficulty occurs.

5. Fire and Explosion Data

Flash Point (Method Used): NAP

Flammable Limits:

LEL: See below under "Unusual Fire and Explosion Hazards"

UEL: NAP

Extinguishing Media: Water, carbon dioxide, sand.

Autoignition Temperature: Variable [typically 400-500° F (204-260°C)]

Special Firefighting Procedures: Use water to wet down wood dust to reduce the likelihood of ignition or dispersion of dust into the air. Remove burned, charred or wet dust to open, secure area after fire is extinguished.

Unusual Fire and Explosion Hazards: Depending on moisture content and more importantly, particle diameter, wood dust may explode in the presence of an ignition source. An airborne concentration of 40 grams (40,000 mg) of dust per cubic meter of air is often used as the LEL for wood dusts.

6. Accidental Release Measures

Steps to be Taken In Case Material Is Released or Spilled: Wood dust may be vacuumed or shoveled for recovery or disposal. Avoid dusty conditions and provide good ventilation. Use NIOSH/MSHA-approved dust respirator and goggles where ventilation is not possible.

Other Precautions: Avoid open flame and contact with oxidizing agents. A NIOSH/MSHA-approved dust respirator and goggles should be worn when the allowable exposure limits may be exceeded.

7. Handling and Storage

Precautions to be Taken In Handling and Storage: Avoid repeated or prolonged breathing of wood dust. Avoid eye contact and repeated or prolonged contact with skin. Keep in cool, dry place away from open flame.

8. Exposure Control Measures

Personal Protective Equipment:

RESPIRATORY PROTECTION -- A NIOSH/MSHA-approved dust respirator is recommended when allowable exposure limits may be exceeded.

PROTECTIVE GLOVES -- Not required. However, cloth, canvas, or leather gloves are recommended to minimize potential mechanical irritation from handling product.

EYE PROTECTION -- Goggles or safety glasses are recommended in areas with high dust levels.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT -- Outer garments may be desirable in extremely dusty areas.

WORK/HYGIENE PRACTICES -- Follow good hygienic and housekeeping practices.

Clean up areas where wood dust settles to avoid excessive accumulation of this combustible material. Minimize blowdown or other practices that generate high airborne-dust concentrations.

Ventilation:

LOCAL EXHAUST -- Provide local exhaust as needed so that exposure limits are met.

MECHANICAL (GENERAL) -- Provide general ventilation in processing and storage areas so that exposure limits are met.

SPECIAL -- Self-contained breathing apparatus (SCBA) recommended when fighting fire.

OTHER -- None.

9. Physical/Chemical Properties

Boiling Point (@ 760 mm Hg):	NAP
Vapor Pressure (mm Hg):	NAP
Vapor Density (air = 1; 1 atm):	NAP
Specific Gravity (H₂O = 1):	Variable; depends on wood species and moisture
Melting Point:	NAP
Evaporation Rate (Butyl acetate = 1):	NAP
Solubility in Water (% by weight):	Insoluble
% Volatile by Volume [@ 70°F (21°C)]:	NAP
pH:	NAP

10. Stability and Reactivity

Stability: () Unstable () Stable

Conditions to Avoid: Avoid open flame. Product may ignite at temperatures in excess of 400°F (204°C).

Incompatibility (Materials to Avoid): Avoid contact with oxidizing agents. Avoid open flame. Product may ignite at temperatures in excess of 400°F.

Hazardous Decomposition or By-Products: Thermal decomposition products include carbon monoxide, carbon dioxide, aliphatic aldehydes, rosin acids, terpenes, and polycyclic aromatic hydrocarbons.

Hazardous Polymerization: () May occur () Will not occur

11. Toxicological Information

Wood dust (softwood or hardwood) OSHA Hazard Rating = 3.3; moderately toxic with probable oral lethal dose to humans being 0.5-5 g/kg (about 1 pound for a 70 kg or 150 pound person). Source: *OSHA Regulated Hazardous Substances*, Government Institutes, Inc., February 1990.

12. Ecological Information

No information available at this time.

13. Disposal Considerations

Waste Disposal Method: If disposed of or discarded in its purchased form, incineration is preferable. Dry land disposal is acceptable in most states. It is, however, the user's responsibility to determine at the time of disposal whether your product meets RCRA criteria for hazardous waste. Follow applicable federal, state, and local regulations.

14. Transport Information

Not regulated as a hazardous material by the U.S. Department of Transportation.

15. Regulatory Information

It is the user's responsibility to determine what regulatory information is relevant to the usage of this product.

16. Additional Information

Date Prepared: 12/10/85

Date Revised: 01/29/01

Prepared By: Safety & Health Risk Management

User's Responsibility: The information contained in this Material Safety Data Sheet is based on the experience of occupational health and safety professionals and comes from sources believed to be accurate or otherwise technically correct. It is the user's responsibility to determine if this information is suitable for their applications and to follow safety precautions as may be necessary. The user has the responsibility to make sure that this sheet is the most up-to-date issue.

Definition of Common Terms:

ACGIH = American Conference of Governmental Industrial Hygienists

C = Ceiling Limit

CAS# = Chemical Abstracts System Number

EPA = U.S. Environmental Protection Agency

IARC = International Agency for Research on Cancer

LCLo = Lowest concentration in air resulting in death

LC50 = Concentration in air resulting in death to 50% of experimental animals

LDLo = Lowest dose resulting in death

LD50 = Administered dose resulting in death to 50% of experimental animals

MSHA = Mining Safety and Health Administration

NAP = Not Applicable

NAV = Not Available

NIOSH = National Institute for Occupational Safety and Health

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

PEL = Permissible Exposure Limit

STEL = Short-Term Exposure Limit (15 minutes)

16. Additional Information (cont)

TCLo = Lowest concentration in air resulting in a toxic effect
TDLo = Lowest dose resulting in a toxic effect
TLV = Threshold Limit Value
TWA = Time-Weighted Average (8 hours)
WHMIS = Workplace Hazardous Materials Information System