

# Contour Series Door® Construction Specifications - Hollow Core

Non-Rated (WCHC-1)

**Product Features  
and Specifications**

**Interior Only (1)**

<b>Thickness</b>	1-3/4" or 1-3/8"
<b>Maximum Size</b>	See Individual Face Profile Chart
<b>Minimum Size</b>	See Individual Face Profile Chart
<b>Faces</b>	1/8" High Density Fiberboard (HDF)
<b>Style</b>	Cremona, Caiman, Clermont, Classique, Coventry, Carmelle, Colonist, Cararra
<b>Stiles</b>	1-1/4" Mill Option WoodStile
<b>Top &amp; Bottom Rails</b>	<b>Standard:</b> 1-7/8" Mill Option Wood <b>Optional:</b> MDF
<b>Face Assembly Adhesive</b>	Type 1
<b>Core (2)</b>	Hollow Core
<b>Maximum Size of Lite Openings</b>	Not Applicable
<b>Other Detail Work</b>	Machining (3)
<b>Factory Finish</b>	Prime Only Opaque
<b>Bifolds</b>	Available (4,5,6), See Individual Face Profile Chart For Details
<b>Warranty</b>	One year llimited, Five year optional (1)

(1) Use of Marshfield DoorSystems, Inc. doors in exterior applications is not recommended and not warranted

(2) Blocking behind panels for support. Blocking is cardboard, polystyene or particleboard. One particleboard lock blocks standard in every door.

(3) Basic factory machining available including machining for hinges, cylindrical locks and card locks.

(4) **All Bottom Rail measurements in Bifolds will be 1" shorter than the measurement listed in the individual Face Profile Chart in order to accommodate track and hardware.**

(5) Outer stile measurments may vary 1/4" (depending on pre-fit).

(6) All bifolds are boxed (or end capped) with track and hardware included.

The mark of excellence™ 

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.



For more information call: 800-869-3667

Marshfield Signature Series doors meet WDMA grade and AWI custom grade standards. ©2005 Marshfield DoorSystems, Inc.