

Contour Series Door® Construction Specifications - Mineral Core

45-Minute Neutral Pressure (WCMC-45), 45-Minute Frame Mounted Positive Pressure (WCMC-45PPFM) (1), 60-Minute Neutral Pressure (WCMC-60), and 60-Minute Frame Mounted Positive Pressure (WCMC-60PPFM) (1)

Product Features and Specifications	Interior Only (2)
Thickness Maximum Size	1-3/4" WCMC-45: See Individual Face Profile Chart WCMC-60: See Individual Face Profile Chart WCMC-45PPFM: See Individual Face Profile Chart WCMC-60PPFM: See Individual Face Profile Chart
Minimum Size	2/0 x 6/8
Faces	1/8" High Density Fiberboard (HDF)
Style	Cremona, Caiman, Clermont, Classique, Coventry, Carmelle, Colonist, Cararra
Stiles	1-1/4" Mill Option Wood
Top & Bottom Rails	Standard: 1-1/48" Mill Option Wood Optional: Wood in customer specified widths
Face Assembly Adhesive Core	Type 1 Asbestos free incombustible mineral core
Maximum Size of	
Lite Openings	Not Applicable
Other Detail Work	Machining (3)
Factory Finish	Prime Only
	Opaque
Bifolds	See Individual Face Profile Chart For Details
Warranty	One year llimited, Five year optional (2)

(1) Meets UBC 7-2-97 positive pressure requirements when frame mounted intumescent is used.
 (2) Use of Marshfield DoorSystems, Inc. doors in exterior applications is not recommended and not warranted.
 (3) Basic factory machining available including machining for hinges, cylindrical locks and card locks.



Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.