

Contour Series Door® Construction Specifications - Mineral Core

45-Minute Neutral Pressure (WCMC-45), 45-Minute Frame Mounted Positive Pressure (WCMC-45PPFM) (1), 60-Minute Neutral Pressure (WCMC-60), and 60-Minute Frame Mounted Positive Pressure (WCMC-60PPFM) (1)

**Product Features
and Specifications**

Interior Only (2)

<p>Thickness Maximum Size</p> <p>Minimum Size</p> <p>Faces</p> <p>Style</p> <p>Stiles</p> <p>Top & Bottom Rails</p> <p>Face Assembly Adhesive</p> <p>Core</p> <p>Maximum Size of</p> <p>Lite Openings</p> <p>Other Detail Work</p> <p>Factory Finish</p> <p>Bifolds</p> <p>Warranty</p>	<p>1-3/4"</p> <p>WCMC-45: See Individual Face Profile Chart WCMC-60: See Individual Face Profile Chart WCMC-45PPFM: See Individual Face Profile Chart WCMC-60PPFM: See Individual Face Profile Chart</p> <p>2/0 x 6/8</p> <p>1/8" High Density Fiberboard (HDF)</p> <p>Cremona, Caiman, Clermont, Classique, Coventry, Carmelle, Colonist, Cararra</p> <p>1-1/4" Mill Option Wood</p> <p>Standard: 1-1/48" Mill Option Wood Optional: Wood in customer specified widths</p> <p>Type 1 Asbestos free incombustible mineral core</p> <p>Not Applicable</p> <p>Machining (3)</p> <p>Prime Only</p> <p>Opaque</p> <p>See Individual Face Profile Chart For Details</p> <p>One year llimited, Five year optional (2)</p>
---	--

(1) Meets UBC 7-2-97 positive pressure requirements when frame mounted intumescent is used.
 (2) Use of Marshfield DoorSystems, Inc. doors in exterior applications is not recommended and not warranted.
 (3) Basic factory machining available including machining for hinges, cylindrical locks and card locks.



Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.