

Contour Series Door® Door Specifications - Particleboard Core

Non-Rated (WCPC-1), 20-Minute Neutral Pressure (WCPC-20), and 20-Minute Frame Mounted Positive Pressure (WCPC-20PPFM) (1)

Product Features and Specifications

Interior Only (1)

Thickness	<p>WPC-1: 1-3/4" or 1-3/8"</p> <p>WCPC-20: 1-3/4"</p> <p>WCPC-20PPFM:1-3/4"</p>						
Maximum Size	<p>WPC-1: See Individual Profile Chart</p> <p>WCPC-20: See Individual Profile Chart</p> <p>WCPC-20PPFM:See Individual Profile Chart</p>						
Minimum Size	See Individual Profile Chart						
Faces	1/8" High Density Fiberboard (HDF)						
Style	Cremona, Caiman, Clermont, Classique, Coventry, Carmelle, Colonist, Cararra						
Stiles (3)	<table border="0"> <tr> <td>WPC-1: 1-3/8":</td> <td>1-1/4" Mill Option Fir</td> </tr> <tr> <td>WCPC-20: 1-3/4":</td> <td>1-1/4" Mill Option Fir</td> </tr> <tr> <td>WCPC-20PPFM:1-3/4"</td> <td>1-1/4" Mill Option Fir</td> </tr> </table>	WPC-1: 1-3/8":	1-1/4" Mill Option Fir	WCPC-20: 1-3/4":	1-1/4" Mill Option Fir	WCPC-20PPFM: 1-3/4"	1-1/4" Mill Option Fir
WPC-1: 1-3/8":	1-1/4" Mill Option Fir						
WCPC-20: 1-3/4":	1-1/4" Mill Option Fir						
WCPC-20PPFM: 1-3/4"	1-1/4" Mill Option Fir						
Top & Bottom Rails (3,4)	<table border="0"> <tr> <td>WPC-1: 1-3/8":</td> <td>7/8" Mill Option Fir</td> </tr> <tr> <td>WCPC-20: 1-3/4":</td> <td>2-5/8" Mill Option Fir</td> </tr> <tr> <td>WCPC-20PPFM:1-3/4:</td> <td>2-5/8" Mill Option Fir</td> </tr> </table>	WPC-1: 1-3/8":	7/8" Mill Option Fir	WCPC-20: 1-3/4":	2-5/8" Mill Option Fir	WCPC-20PPFM: 1-3/4:	2-5/8" Mill Option Fir
WPC-1: 1-3/8":	7/8" Mill Option Fir						
WCPC-20: 1-3/4":	2-5/8" Mill Option Fir						
WCPC-20PPFM: 1-3/4:	2-5/8" Mill Option Fir						
Face Assembly Adhesive Core	Type 1 28 pounds per cubic foot-minimum-density particleboard core						
Maximum Size of Lite Openings	Not Applicable						
Other Detail Work	Machining (5)						
Factory Finish	Prime Only Opaque						
Bifolds	Available (7,8,9), See Individual Face Profile Chart For Details						
Warranty	One year limited, Five year optional (2)						

- (1) Meets UBC 7-2-97 positive pressure requirements when frame mounted intumescient is used.
- (2) Use of Marshfield DoorSystems, Inc. doors in exterior applications is not recommended and not warranted
- (3) MDF rails with millioption wood is the standart option. All wood frame is an available option and must be requested.
- (4) Optional wood top and bottom rails available in customer-specified widths.
- (5) Basic factory machining available includingd machining for hinges, cylindrical locks and card locks.
- (6) All bottom rail measurements in bifolds will be one inch shorter than the measurement listed in the chart above in order to accomodate track and hardware**
- (7) Outher stile measurements may vary 1/4" (depending on pre-fit)
- (8) All bifolds are boxed (or end-capped) with track and hardware included.

The mark of excellence™ 

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.



For more information call: **800-869-3667**
Marshfield Signature Series doors meet WDMA grade and AWI custom grade standards. ©2005 Marshfield DoorSystems, Inc.