


Applied Mouldings

Applied Mouldings

Marshfield DoorSystems offers four standard applied mouldings. They are:



Profile 5 is the applied moulding that will be used on the Marshfield DoorSystems Styled™ Door unless specified otherwise. Additional custom mouldings are available to suit any project. (An upcharge for custom moulding will apply and additional lead-time is required.) Mouldings are available in most species of lumber.

- Unfinished and primed doors will not have nail holes filled.
- Modified #5 Moulding will be used as standard on Workable Surface Doors with surface applied mirrors, white boards, or cork board.
- Factory finished doors with applied mouldings will have nail holes filled.

Applied Mouldings for Fire Doors (2)

	UL 20-minute	UL 45-90-minute	ITS-WH 20-minute	ITS-WH 45-90-minute
Maximum Size	No Limit	1-1/2" x 3/4"	No Limit	1-1/2" x 3/4"
Application Method	Glue	Glue	Glue	Glue
Minimum Distance between Parallel Moulding Pieces	No Limit	3"	No Limit	3"
Minimum Distance between Lite and Applied Moulding	No Limit	No Limit	3-1/2"	3-1/2"
Minimum Distance between Door Edge and Moulding (1)	1"	1"	1"	1"

(1) Moulding must not interfere with the operation of the door, hardware or accessories.

(2) Installation of applied moulding on doors with either UL or ITS-WH labels must be done by Marshfield DoorSystems or a licensed machiner.

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.