

Staved Lumber Core Doors

Neutral Pressure (12) - NON-RATED (DSC-1) and 20-MINUTE (DFS-20)

| Product Features and Specifications | Interior Only (1) |
|---|---|
| Thickness | 1-3/4", 2", 2-1/4" |
| Maximum Size | DSC-1: Single: 4/0 x 10/0 Pair: 8/0 x 10/0 DFS-20: ITS-WH & UL: Single: 4/0 x 10/0 Pair: 8/0 x 10/0 Double Egress Pair: 8/0 x 8/0 |
| Minimum Size | 0/8 x 1/10 (32) |
| Faces | <ul style="list-style-type: none"> • Wood Veneer • Primed MDO • Decorative Laminate • Styled® Door Face |
| Crossbands | Engineered fiber |
| Stiles | 1" LSL with veneer band or decorative laminate to match face (2,3) |
| Top and Bottom Rails | 7/8" (after trim) Mill Option (4,5,24,25) |
| Face Assembly Adhesive | Type I (waterproof) |
| Core Assembly Adhesive | Type II (water-resistant) |
| Core | Butt-jointed staved lumber core |
| Maximum Size of Lite Openings (6,33) | <p>METAL VISION FRAMES or WOOD MOULDING: DSC-1: (9) (10) Total area of openings not to exceed 1,296 sq. in. of visible glass or one continuous dimension of 38" W or 54" H</p> <ul style="list-style-type: none"> •See Glazing Table |
| Other Detail Work (7, 21) | <ul style="list-style-type: none"> • Fitting • Machining • Applied Mouldings •Dutch •Transom •Reveals •Radius Lites <p>Only available in DSC-1: •Wicket •Divided Lite •Stain Glass •Embossed Glass •Custom Lite</p> <ul style="list-style-type: none"> •Grilles |
| Factory Finish (8) | <ul style="list-style-type: none"> • Clear or Stain w/ Enviroclad UV® finish • Prime • Opaque with flat gloss topcoat |
| Warranty | Full; life of original installation (1) |
| Security Rating | Class 40 (9) , highest Security Rating possible |
| Acoustic Rating (11) | STC 31 (Inoperable) |

*Refer to separate page for explanation of footnotes.