

Staved Lumber Core Doors

Positive Pressure with Frame Mounted Intumescent (13) (14) - 20-MINUTE (DFS-20PPFM)

Product Features and Specifications	Interior Only (1)
Thickness	1-3/4", 2", 2-1/4"
Maximum Size	ITS-WH & UL: Single: 4/0 x 10/0 Pair: 8/0 x 9/0 (65) DFS-20PPFM: Double Egress Pair: 8/0 x 9/0 (65)
Minimum Size	0/8 x 1/10 (32)
Faces	<ul style="list-style-type: none"> • Wood Veneer • Primed MDO • Decorative Laminate • Styled® Door Face
Crossbands	Engineered fiber
Stiles	1" LSL with veneer band or decorative laminate to match face (2,3)
Top and Bottom Rails	7/8" (after trim) Mill Option (4,5,24,25)
Face Assembly Adhesive	Type I (waterproof)
Core Assembly Adhesive	Type II (water-resistant)
Core	Butt-jointed staved lumber core
Lite Openings (6)	See Glazing Table
Other Detail Work (7,10,21,35)	<ul style="list-style-type: none"> • Fitting • Machining • Applied Mouldings • Dutch Doors • Transoms • Reveals • Radius Lites
Factory Finish (8)	<ul style="list-style-type: none"> • Clear or Stain w/ Enviroclad UV® finish • Prime • Opaque with flat gloss topcoat
Warranty	Full; life of original installation (1)
Security Rating	Class 40 (9) , highest Security Rating possible
Acoustic Rating (11)	STC 31 (Inoperable)

*Refer to separate page for explanation of footnotes.