Stile & Rail Doors

Positive Pressure and Neutral Pressure - 20 Minute (WSR-20 PP) and 90 Minute (WSR-90 PP-NP)

Product Features and Specifications	WSR-20 PP - **Interior Only (1) (3)**	WSR-90 PP NP - **Interior Only (1) (3)**
Thickness	1-3/4", 2", 2-1/4"	2-1/4"
Maximum Size	**Single:** 3/6 x 8/0 **Pair:** 7/0 x 8/0	Same
Minimum Size	1'-3 1/4" x 1'-10 1/16"	1'-4 1/4" x 1'-10 7/8"
Faces: Wood Veneer	Panels 1/40", elsewhere 1/20"	Same
Stile Edge	Matching Veneer Bands	Same
Sticking & Stops	Matching Wood	Same
Core Material	MDF	Mineral
Adhesives	Type 1 (waterproof)	Same
Joinery	Tongue & groove plus dowels	Tongue & groove
Panel Construction		
Raised 1 side	N/A	N/A
Raised 2 sides	1-1/4"	1-7/8"
Flat	5/8"	1-1/4"
Step	N/A	N/A
Step Rim	N/A	N/A
Panel Size	Minimum: 5-1/8" x 8-9/16" Maximum: 26" x 52"	Minimum: 6-1/8" x 9-3/8" Maximum: 32" x 46-3/4"
Stock Dimensions		
Top Rail	5"	5"
Center Rails	3-5/8"	4"
Lock Rail	7-3/4"	8"
Bottom Rail	8-1/2"	8-1/2"
Mullions	3-5/8"	4"
Muntins	N/A	N/A
Stiles	5-1/16"	5-1/16"
Bottom of door to: top of lock rail	39" or specify	Same
Lite Opening (6)	Factory glazed: wired, FireLite® Plus or NT,1040 Sq. In. max.	N/A
Other Detail Work	• Fitting • Machining **(7,21,23)**	Same **(21,7,23)**
Factory Finish	• Clear • Stain **(8)** • Prime • Paint **(8)**	Same
Warranty (1)	Limited Life: original installation	Same
Acoustic Rating	N/A	N/A

*Refer to seperate page for explanation of footnotes.

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

©2005 Marshfield DoorSystems, Inc.