


Stile & Rail Doors

Positive Pressure, Neutral Pressure, Environmental

Marshfield Signature Series®

Standard Models: WSR

 Environmental Models: EWSR, EWSRUF

Product Features and Specifications	45 Minute PP or NP - Interior Only	60 Minute PP or NP - Interior Only
Thickness	1-3/4", 2", 2-1/4"	Same
Maximum Size	Single: 3/6 x 8/0 Pair: 7/0 x 8/0	Same
Minimum Size	1/4 x 1/5	Same
Faces:	Wood Veneer	Same
Stile Edge	Matching Wood	Same
Sticking & Stops	Matching Wood	Same
Core Material	Composite	Same
Adhesives	Type 1 (waterproof)	Same
Joinery	Doweled	Same
Panel Construction		
Raised 1 side	N/A	N/A
Raised 2 sides	1-5/32"	1-9/16"
Flat	15/16"	7/8"
Step	1-5/32"	N/A
Step Rim	1-5/32"	N/A
Panel Size	Minimum: 6 x 6" Maximum: 32" x 85"	Minimum: Same Maximum: 26" x 46-3/4"
Stock Dimensions		
Top Rail	5"	Same
Center Rails	3-5/8"	Same
Lock Rail	7-3/4"	Same
Bottom Rail	8-1/4"	Same
Mullions	3-5/8"	Same
Muntins	N/A	Same
Stiles	5-1/16"	Same
Bottom of door to:		
top of lock rail	39" or specify	Same
Lite Opening	Factory glazed: wired, FireLite® Plus or NT, 1,216sq in max, max width 26" max height 48"	Same
Other Detail Work	• Fitting • Machining	Same
Factory Finish	• Clear • Stain	
	• Prime • Paint	
Warranty	Limited Life: original installation	Same
Acoustic Rating	N/A	N/A
Environmental Options & LEED Credit Contributions	• MR 4 - Recycled Content — all models • MR 7 - Certified Wood — contact Sales Center • IEQ 4.4 - Low-Emitting Materials — all UF models No Added Urea Formaldehyde Resins	• MR 4 - Recycled Content — all models • MR 7 - Certified Wood — contact Sales Center • IEQ 4.4 - Low-Emitting Materials — all UF models No Added Urea Formaldehyde Resins

The mark of excellence™ 

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.