Stile & Rail Doors

Positive Pressure and Neutral Pressure - 45 MINUTE (WSR-45 PP-NP) and 60 MINUTE (WSR-60 PP-NP)

Product Features and Specifications	WSR-45 PP-NP - **Interior Only (1) (31)**	WSR-60 PP-NP - **Interior Only (1) (31)**
Thickness	1-3/4", 2", 2-1/4"	Same
Maximum Size	**Single:** 3/6 x 8/0 **Pair:** 7/0 x 8/0	Same
Minimum Size	1'- 4 1/4" x 1'-10 7/8"	Same
Faces: Wood Veneer	Panels 1/40", elsewhere 1/20"	Same
Stile Edge	Matching Veneer Bands	Same
Sticking & Stops	Matching Wood	Same
Core Material	Mineral	Same
Adhesives	Type 1 (waterproof)	Same
Joinery	Tongue & groove	Same
Panel Construction		
Raised 1 side	N/A	N/A
Raised 2 sides	1-9/16"	1-9/16"
Flat	7/8"	7/8"
Step	N/A	N/A
Step Rim	N/A	N/A
Panel Size	Minimum: 6-1/8" x 9-3/8" Maximum: 32" x 46-3/4"	Minimum: Same Maximum: 26" x 46-3/4"
Stock Dimensions		
Top Rail	5"	Same
Center Rails	4"	Same
Lock Rail	8"	Same
Bottom Rail	8-1/2"	Same
Mullions	4"	Same
Muntins	N/A	Same
Stiles	5-1/16"	Same
Bottom of door to: top of lock rail	39" or specify	Same
Lite Opening (6)	Factory glazed: wired, FireLite® Plus or NT, 3 lites, 100 Sq. In. ea. max.	Same
Other Detail Work	• Fitting • Machining **(7,21,23)**	Same **(21,7,23)**
Factory Finish	• Clear • Stain **(8)** • Prime • Paint **(8)**	
Warranty (1)	Limited Life: original installation	Same
Acoustic Rating	N/A	N/A

*Refer to seperate page for explanation of footnotes.

Note: Marshfield DoorSystems, Inc. doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.

©2005 Marshfield DoorSystems, Inc.