

# PerfectMatch™ Particleboard Core Doors

NON-RATED (PMP-1) and 20-MINUTE POSITIVE PRESSURE (PMP-20PPFM - SINGLES and PMP - 20PP PAIRS) (13)

## Product Features and Specifications

## Interior Use Only

<b>Thickness</b>	1-3/4"
<b>Maximum Size</b>	<b>PMP-1:</b> <b>Single:</b> 4/0 x 8/0 <b>Pair:</b> 8/0 x 8/0 <b>PMP-20 PPFM:</b> <b>ITS-WH and UL:</b> <b>Single:</b> 4/0 x 8/0 <b>PMP-20PP:</b> <b>ITS-WH and UL:</b> <b>Pair:</b> 4/0 x 8/0 (15) <b>Double Egress:</b> 8/0 x 8/0 (15)
<b>Minimum Size</b>	1-5 3/4 x 6/0
<b>Faces</b>	Thermoset Polymer
<b>Crossbands</b>	Engineered Fiber
<b>Stiles</b>	<b>PMP-1 and PMP-20PPFM:</b> 1" LSL with edge banding or stained stiles to match face <b>PMP-20PP:</b> 1-3/8" concealed Intumescent stiles with edge banding or stained stiles to match face
<b>Top and Bottom Rails</b>	7/8" Mill Option                Wider top & bottom rails available
<b>Core Assembly Adhesive</b>	Type II (water-resistant)
<b>Core</b>	Particleboard
<b>Lite Openings (6)</b>	<b><u>METAL VISION FRAMES OR WOOD MOULDING:</u></b> W2 - W3 or W10 <b>PMP-1:</b> Total area of openings not to exceed 1,296 sq. in. of visible glass or one continuous dimension of 38" W or 54" H  <ul style="list-style-type: none"> <li>• See Glazing Table</li> </ul>
<b>Other Detail Work (7, 10, 21)</b>	<ul style="list-style-type: none"> <li>• Fitting   • Machining</li> </ul>
<b>Warranty</b>	Limited Lifetime

\*Refer to separate page for explanation of footnotes.