

Packaging and Weights

Appendix E

Packaging

Doors are palletized in quantities determined by the number ordered and size. Stretch wrapping, sheet corrugated cardboard and banding are combined to give you superior packaging to protect your doors. For an additional cost, doors may be individually protected with polywrap cardboard cartons and specially packaged for jobsite delivery and coordination. When delivered by common carrier, doors are packaged using specially reinforced materials.

Bottom board palletizing is available. When selecting the bottom board palletizing service, Marshfield DoorSystems® will add a 7/16" Oriented Strand Board (OSB) to the bottom of the door pallet, offering an extra layer of protection.

Weights

Approximate Weights per Square Foot by Door Type

1-3/4" Particleboard Core	5.5 lbs
1-3/8" Particleboard Core	4.4 lbs
1-3/4" Mineral Core (45, 60, 90-minute)	3.7 lbs
1-3/4" Structural Composite Lumber Core	6.9 lbs
1-3/4" Staved Core	4.6 lbs
2-1/4" Staved Core	5.9 lbs
1-3/4" Sound Retardant (DSR41)	7.1 lbs
1-3/4" Stile and Rail	6.0 lbs
1-3/4" Radiation Shielded 1/16" Lead Lined	9.5 lbs
1-3/4" Extra Heavy Duty ParticleBoard	8.0 lbs

Note: Marshfield DoorSystems® doors are manufactured per the standards listed on this page. Specifications are subject to change without notice.